

# marian

DIGITAL AUDIO ELECTRONICS

## Widest Selection of Digital and Analog Sound Cards



**Marc 4 MIDI** 4x analog in, 4x analog out soundcard, 24 Bit 96kHz converters, MIDI in-and-out cable (not shown).



**Marc 2 Pro** Stereo 24 Bit 96kHz soundcard. Balanced analog in and out, digital in and out: AES/EBU on XLR, SPDIF on coax RCA and optical TOSLINK; BNC word-clock in. Audio in and out via break-out cable (not shown). Includes MARC4 Extender.



**Marc A** 8-channel 24bit/48kHz ADAT I/O soundcard. TOSLINK light-pipe interface.



**Marc 2** Stereo 24 Bit 96kHz soundcard, unbalanced analog in and out, digital in and out SPDIF coax on RCA and TOSLINK optical.



**Marc 4 DIGI** 4x analog in, 4x analog out soundcard, 24 Bit 96kHz converters, with stereo SPDIF on TOSLINK optical in and out.



**Marc 4 Extender** extender for MARC 4 DIGI soundcard, stereo digital SPDIF on RCA, AES/EBU on XLR, word-clock in.



**Marc 8 MIDI** 8x analog in, 8x analog out soundcard, 24 Bit 96kHz, with 2x MIDI in and out.

All MARIAN soundcards include the following drivers: Windows® 95/98/ME, Windows NT®4.0, Windows® 2000, Windows® XP, Windows® MME, ASIO™ 2.0, GSIF, Direct Sound. Also included is a free copy of the award winning *Samplitude Project 5.9*



**ADCON** 8-channel 24 Bit, 48kHz analog to digital and digital to analog converter, balanced in and out, 2 mic pre inputs with phantom power, digital ADAT light pipe interface.

All company and product names mentioned herein may be trademarks or registered trademarks of their respective owners.

